MATERIAL SAFETY DATA SHEET

MSDS #: M600-E

Page 1 of 3

Sanford NA 2707 Butterfield Road

Oak Brook, IL 60523

Phone: 630-481-2000 or 800-323-0749

Emergency Medical Number: 888-786-0972

Creation Date:

August 1, 2005

		RCUD JAN 2007			409832		
Section One:	Product Inform						
Product Name:	Max Grumbacher Artists' O	il Color					
Product Sizes:	7.5, 24, 37, and 150 ml						
Product Class:	Artists' Oil Color						
Section Two:	Ingredients						
Ingredients		CAS Number	% by Weight	PEL/TLV			
Linseed Oil		8001-26-1	62.0%	N/A	2	5 s	
Nickel Pigment		N/A	10.0%	N/A			
			=				
	27 O				• 0		
ection Three:	Hazards Identi	fication		*			

^{**}WARNING: This product contains a chemical known to the State of California to cause cancer.

Se	ction Four:	First Aid Measures		13.47	
¥	Inhalation:	None under normal use conditions.			
	Skin Contact:	None under normal use conditions.			
	Eye Contact:	None under normal use conditions.			
	Ingestion:	None under normal use conditions.			

This Material Safety Data Sheet is applicable to the consumer use of the following colors: M166, M187

Page 2 of 3

Section Five:

Fire Fighting Measures

Flash Point:

Not flammable

Flammability Limits (% by volume):

Lower: Not explosive

Not explosive Upper:

Extinguishing Media:

As appropriate for surrounding area.

Special Fire Fighting Measures:

No special fire fighting procedures.

Unusual Fire and Explosion

Hazards:

Not combustible

Section Six:

Accidental Release Measures

No special spill procedures required

Section Seven:

Handling and Storage

Handling:

No special handling requirements.

Storage:

No special storage requirements.

Section Eight:

Exposure Controls and Personal Protection

Respiratory Protection and

Special Ventilation Requirements:

None required

Other Protective Equipment (Gloves, Goggles, Etc.):

None

Work/Hygiene Practices:

Studio hygiene rules should be observed. Wash thoroughly before eating, drinking, or smoking.

Section Nine:

Physical and Chemical Properties

Boiling Point:

Not determined

Melting Point:

Not determined

Vapor Pressure:

Not determined

Specific Gravity:

Not determined

Specific Vapor Density (AIR = 1):

Not determined

Evaporation Rate (Butyl Acetate = 1):

Not determined

Solubility in Water:

Not determined

Reactivity in Water:

Non-reactive

Appearance and Odor:

Colored paints; oily odor

Section Ten:

Stability and Reactivity

Stability:

Stable

Conditions to Avoid:

Excessive heat

Chemical Incompatibility:

None known

Hazardous Decomposition:

None known

Hazardous Polymerization:

Will not occur

Page 3 of 3

Section Eleven:

Toxicological Information

IARC Monographs:

No

National Toxicology Program:

No

OSHA Regulated:

No

Effects/Symptoms of

Acute Exposure:

None expected

Effects/Symptoms of

None expected

Chronic Exposure:

Medical Conditions Usually Aggravated By Overexposure of This Product:

None known

Section Twelve:

Ecological Information

Not available

Section Thirteen:

Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen:

Transport Information

Not regulated as a hazardous material by DOT, IMO, or IATA.

Section Fifteen:

Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen:

Other Information

HMIS Code

Health

0

Flammability Reactivity 0

Personal Protection

0 N/A Sanford Corporation is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.